Taymor | PRODUCT SPECIFICATIONS

GRADE 2 DEADBOLTS

FEATURES

- ANSI/BHMA A 156.2 GRADE 2
- SOLID BRASS CYLINDER
- DOOR PREP: CROSS BORE 2-1/8" (54 mm)
- 2-IN-1 ADJUSTABLE BACKSET LATCH
- 2-3/8" TO 2-3/4" [61 mm x 70 mm]
- 1 1/8" x 2-1/4" (25 mm x 57 mm) SQUARE MORTISE LATCH

1-3/8"-1-3/4" (35 mm - 45 mm)

3/8" (9 mm)

(26 mm)

- 5 YEAR MECHANICAL WARRANTY
- 3-HOUR FIRE RATED



SINGLE CYLINDER DEADBOLT

ROUND ROSE

Ø2-1/2







2-1/8" (54 mm)

MEETS ADA STANDARDS.

ANSI GRADE 2



FULL KEYING SERVICES AVAILABLE

6-pin SC4 keyway, packaged keyed different



FIRE RATED


Meets c-UL and UL 3-hour fire rating standard

2-IN-1 LATCH


Ø2-1/2" (65 mm)

(0

1" (25 mm)



A. SINGLE CYLINDER DEADBOLT RADIUS & SQUARE STRIKES



COMMERCIAL GRADE 2 DEADBOLT	19 MATTE BLACK	26D SATIN CHROME	32D SATIN STAINLESS STEEL	CASE PACK
SINGLE CYLINDER DEADBOLT	32-F480BLK	32-F470	32-F450	20

